IN THE CLAIMS:

Please amend the claims as follows:

 (Currently Amended) A method for extracting commands and acoustic data in a same utterance, comprising the steps of:

decoding at least one word in acoustic data representing an acoustic signal that

comprises a human utterance and determining acoustic word boundaries within the acoustic

data;

extracting at least one explicit command in a decoded utterance using a current recognition vocabulary;

extracting, in the decoded utterance using the current recognition vocabulary, at least one implicit command related to the at least one explicit command;

changing to a different recognition vocabulary responsive to the at least one implicit command; and

identifying acoustic data segments in the utterance that are data parts of at least the at least one explicit implicit command based on the acoustic word boundaries and using at least the different recognition vocabulary.

 (Original) The method as recited in claim 1, wherein the step of determining acoustic word boundaries includes finding segment boundaries by iteratively comparing the same utterance to a plurality of vocabularies.

- (Currently Amended) The method as recited in claim 1, further comprising the step of
 executing the at least one explicit implicit command from the decoded utterance.
- 4. (Currently Amended) The method as recited in claim 3, further comprising at least one of storing the acoustic data segments and using the acoustic data segments in executing the at least one explicit implicit command.
- (Currently Amended) The method as recited in claim 3, further comprising the step
 of submitting at least one non-command voice data segment for recognition using the
 recognizer different recognition vocabulary.
 - 6. (Cancelled)
- 7. (Original) The method as recited in claim 1, further comprising the step of submitting the acoustic data segments for recognition when computing resources are available.
- 8. (Previously Presented) The method as recited in claim 1, wherein the step of extracting at least one explicit command from the utterance includes employing one or more grammars to distinguish the command.
- (Original) The method as recited in claim 8, wherein the grammars include a form for extracting information for an order or verbal contract.

- (Original) The method as recited in claim 8, wherein the grammars include a form for reminding a user to perform a task.
- 11. (Original) The method as recited in claim 8, wherein the grammars include a form for extracting maximum meaningful length segments under interruption or silence conditions.
- 12. (Original) The method as recited in claim 8, wherein the step of using grammars includes the step of associating at least one grammar label with the corresponding segment of acoustic data that has been decoded into a command.
- 13. (Original) The method as recited in claim 12, wherein the label includes a numerical value associated with each command.
- 14. (Currently Amended) The method as recited in claim 1, further comprising the step of executing the at least explicit implicit command in the utterance using undecoded acoustic data from within the same utterance.
- 15. (Original) A program storage device readable by machine, tangibly embodying a program of instructions executable by the machine to perform method steps for processing commands and voice data in a same utterance as recited in claim 1.

16. (Currently Amended) A method for recognizing at least one command and at least one segment of acoustic voice data in a same utterance comprising the steps of:

decoding at least one word in voice data representing the acoustic signal that comprises a human utterance and determining the acoustic word boundaries within the voice data:

extracting at least one <u>explicit</u> command <u>and at least one implicit command</u> from the utterance; <u>and</u>

associating segments in the voice data based on the acoustic word boundaries with labels; and

executing the at least one <u>implicit</u> command utilizing undeseded information in the

acoustic voice data;

wherein the at least one explicit command is extracted using a current recognition vocabulary, and said step of executing the implicit command includes changing a recognizer vocabulary, and

wherein the method further includes decoding undecoded information in the acoustic voice data using the changed recognizer vocabulary.

17. (Original) The method as recited in claim 16, wherein the step of extracting includes employing an application, which identifies commands in the utterance in accordance with the labels.

18. (Cancelled)

- 19. (Original) The method as recited in claim 16, wherein the step of extracting includes the step of storing at least one non-command voice data segment.
- 20. (Currently Amended) The method as recited in claim 16, wherein the step of extracting executing includes calling a vocabulary for recognizing numbers, and said decoding step includes recognizing the numbers in the utterance.
- 21. (Previously Presented) The method as recited in claim 16, wherein the step of extracting includes extracting acoustic data based on acoustic word boundaries and saving the acoustic data for acoustically rendering the acoustic data.
- 22. (Previously Presented) The method as recited in claim 16, wherein the step of extracting includes extracting acoustic data based on acoustic word boundaries and decoding the acoustic data for storage.

23. (cancelled)

- 24. (Original) The method as recited in claim 16, further comprising the step of buffering the utterance to be processed and maintaining the utterance in memory during processing of the utterance.
 - 25. (Previously Presented) The method as recited in claim 16, wherein the step of

associating segments of the word boundaries of the commands with a label includes employing grammars to associate a unique label with each command segment in the utterance.

- 26. (Original) The method as recited in claim 25, wherein the label includes a numerical value.
- 27. (Original) The method as recited in claim 25, wherein the grammars include a form for extracting information for an order or verbal contract.
- 28. (Original) The method as recited in claim 25, wherein the grammars include a form for reminding a user to perform a task.
- 29. (Original) The method as recited in claim 25, wherein the grammars include a form for extracting maximum meaningful length segments under interruption or silence conditions.
- 30. (Original) The method as recited in claim 16, wherein the step of determining the acoustic word boundaries includes finding segment boundaries by iteratively comparing the same utterance to a plurality of vocabularies.
- 31. (Original) A program storage device readable by machine, tangibly embodying a program of instructions executable by the machine to perform method steps for recognizing commands and voice data in a same utterance as recited in claim 16.

32. (Currently amended) A system for recognizing commands and voice data in a same utterance comprising:

an acoustic input, which receives utterances;

- a data buffer configured to store audio data representing the utterances;
- a speech recognition engine configured to match portions of the utterances to acoustic models and language models to recognize words and word boundaries in the utterances and labels commands in the utterances:
- at least one program that <u>identifies explicit commands and implicit commands in the utterances</u>, executes label-identified <u>ones of the explicit commands and the implicit commands</u>, and processes remaining portions of the utterances including processing audio data parts <u>of the implicit command</u> separately from the <u>explicit</u> commands using a different vocabulary, the vocabulary being selected in accordance with <u>the</u> at least one <u>implicit command in the</u> utterance.
- 33. (Original) The system as recited in claim 32, wherein the at least one program includes a function which searches the utterance for labels output from the speech recognition engine to execute a command associated with the label.
- 34. (Original) The system as recited in claim 32, wherein, in accordance with each label, an audio segment is identified and processed.

- 35. (Original) The system as recited in claim 32, wherein the speech recognition engine utilizes grammars with labels, which the system uses for assigning labels to decoded commands.
- 36. (Original) The system as recited in claim 35, wherein the grammars are represented in Bachus-Naur Form (BNF).